




Concept of Managed Aquifer Recharge (MAR)



PUSAT KAJIAN HIDROGEOLOGI
INSTITUT PENYELIDIKAN AIR KEBANGSAAN
MALAYSIA (NAHRIM)
LOT 5377, JALAN PUTRA PERMAI,
43300 SERI KEMBANGAN, SELANGOR

Concept of Managed Aquifer Recharge (MAR)

OLEH:

MOHD KHAIRUL NIZAR BIN SHAMSUDDIN

2025

Managed Aquifer Recharge (MAR)

Managed Aquifer Recharge (MAR) is the process of intentionally augmenting the natural recharge of groundwater by directing water into an aquifer through various techniques, methods, and systems. The goal of MAR is to sustainably increase groundwater levels, improve water quality, and enhance water availability for future use. MAR is especially beneficial in areas facing water scarcity, over-extraction of groundwater, or contamination of aquifers.

Key Objectives of MAR

1. **Increase Groundwater Storage:** MAR helps replenish aquifers by adding water that can be stored for future use, especially during periods of excess water availability (e.g., during rainy seasons).
2. **Improve Water Quality:** By using natural filtration processes within the aquifer, MAR can improve the quality of water, especially when surface water (such as treated wastewater or stormwater) is being recharged.
3. **Enhance Water Supply Reliability:** MAR helps mitigate drought conditions by storing water in aquifers for later extraction, providing a reliable water supply during dry periods.
4. **Prevent Groundwater Depletion:** In areas where groundwater extraction exceeds natural replenishment rates, MAR can help stabilize the water table by reintroducing water into the aquifer.
5. **Reduce Land Subsidence:** Over-extraction of groundwater can lead to land subsidence. MAR helps prevent this by maintaining or raising groundwater levels.

Methods of Managed Aquifer Recharge (MAR)

There are several methods for implementing MAR, depending on the location, groundwater characteristics, and available water sources. Common methods include:

1. **Recharge Wells (Injection Wells):**
 - In this method, water is directly injected into the aquifer through a well. The well is typically equipped with a **perforated casing** or **screen** to allow water to flow into the surrounding rock or sediment. This technique is used when the aquifer is confined, and there is limited natural infiltration.
 - Common in **urban areas** or places with **low-permeability soils**.
2. **Spreading Basins:**
 - Also called **recharge ponds** or **percolation basins**, these are shallow depressions or ponds where water is spread over the surface to allow it to percolate through the soil into the underlying aquifer. This method is effective when the area has permeable soils that allow water to infiltrate quickly.
 - Common in agricultural or rural areas, especially in places with **arid** or **semi-arid** climates.
3. **Infiltration Galleries:**
 - An infiltration gallery is a system of pipes or drains laid below the surface in a horizontal configuration. These pipes are perforated, allowing water to infiltrate the soil and recharge the aquifer. This method is often used in areas with limited surface space or when surface infiltration is not feasible.
4. **Ditches and Canals:**

- Water can be conveyed to recharge areas via open ditches or canals, where it is allowed to infiltrate into the groundwater. This method is often used in agricultural areas with large amounts of surface water available during certain times of the year.
- 5. **Artificial Recharge with Wastewater:**
 - In some cases, treated wastewater (such as from municipal treatment plants) is used for recharge. This is a sustainable practice in water-scarce regions, as it makes use of otherwise discarded water. Wastewater is treated to meet specific standards before being injected into the aquifer.
- 6. **Rainwater Harvesting for Recharge:**
 - In urban or semi-urban areas, rainwater harvesting systems can be used to collect rainwater and direct it to recharge wells or infiltration basins. This method helps capture rainwater that would otherwise flow into stormwater systems or directly to the ocean.

Types of Aquifers for MAR

The effectiveness of MAR depends on the type of aquifer and the geological conditions. Some key factors include:

1. **Unconfined Aquifers:** These aquifers are close to the surface and are naturally recharged by rainfall. MAR can be used to accelerate this process, especially in regions with high groundwater extraction rates.
2. **Confined Aquifers:** These aquifers are isolated by impermeable layers. MAR in confined aquifers often requires **injection wells** since water cannot naturally infiltrate through the confining layer.
3. **Fractured Rock Aquifers:** Aquifers in fractured rock formations often require specialized recharge methods to ensure that water is injected into the fractures and not lost to other areas.
4. **Coastal Aquifers:** Coastal aquifers can benefit from MAR to prevent **saltwater intrusion**. By adding fresh water, the aquifer's pressure is maintained, which helps to prevent the encroachment of saline water into the groundwater system.

Key Benefits of Managed Aquifer Recharge

1. **Enhanced Groundwater Storage:**
 - MAR can significantly increase the amount of water stored in aquifers, which can be accessed during dry periods, improving the overall water security of the region.
2. **Flood Mitigation:**
 - During heavy rainfall or flooding events, MAR systems like spreading basins can capture and store excess water that might otherwise contribute to flooding.
3. **Water Quality Improvement:**
 - Water injected into aquifers is filtered through the soil and geological formations, often improving the quality of the water by removing contaminants and sediment.
4. **Cost-Effective Solution:**
 - In many cases, MAR can be more cost-effective than other water storage methods, such as building large reservoirs. It can also help to maintain water supply reliability without requiring large infrastructure investments.

5. **Prevention of Land Subsidence:**

- In areas where excessive groundwater extraction has caused land subsidence (sinking), MAR can help maintain or restore the natural pressure in the aquifer, preventing further damage to the landscape and infrastructure.

6. **Use of Non-Conventional Water Sources:**

- MAR allows for the use of non-potable water sources (such as treated wastewater, stormwater, and brine) for groundwater recharge, thus reducing reliance on freshwater sources.

Challenges and Considerations of MAR

1. **Water Quality:**

- The quality of the water being injected into the aquifer is crucial. Contaminants in the injected water can degrade groundwater quality. Effective treatment systems must be in place to ensure the water meets safety standards before injection.

2. **Over-extraction Risk:**

- MAR should not be used as a substitute for **sustainable groundwater extraction** practices. The amount of water injected into the aquifer should not exceed the natural replenishment rate.

3. **Clogging of Recharge Systems:**

- Over time, recharge wells and infiltration systems can become clogged by fine sediments, organic matter, or biological growth. Regular maintenance and filtration systems are necessary to keep these systems functioning efficiently.

4. **Geological and Hydrogeological Conditions:**

- The success of MAR depends on the local geological conditions, such as the permeability of the soil, the depth of the aquifer, and the aquifer's ability to accept and store water. In regions with low permeability or confined aquifers, MAR may be more challenging.

5. **Cost and Infrastructure:**

- While MAR can be a cost-effective solution, it still requires significant infrastructure investments for well construction, water treatment, monitoring systems, and maintenance.

Examples of MAR Projects Around the World

1. **California, USA:**

- **Central Valley:** This region has implemented artificial recharge systems, using surface water (including from rivers) to recharge aquifers. In particular, the **Kings River** has been used to direct water into spreading basins, where it is allowed to percolate into the aquifer.

2. **Israel:**

- **Shafdan Wastewater Treatment Plant:** Treated wastewater is used for recharge, improving groundwater levels in the **Coastal Aquifer**, a critical water source for Israel.

3. **Australia:**

- In **Adelaide**, artificial recharge projects use treated water and stormwater to recharge the city's aquifers, which are critical to the region's water supply.

4. **India:**

- In **Tamil Nadu** and **Rajasthan**, MAR has been used to recharge aquifers in rural areas by using check dams, recharge wells, and rainwater harvesting systems.

Literature Review on Managed Aquifer Recharge (MAR)

Introduction to Managed Aquifer Recharge (MAR)

Managed Aquifer Recharge (MAR) refers to the intentional enhancement of groundwater recharge through various methods, including direct injection, surface infiltration, or the use of natural and artificial recharge basins. MAR techniques are designed to optimize the replenishment of aquifers that have been depleted due to excessive water extraction or other environmental stresses. As the global demand for water increases and natural water sources become more stressed, MAR is becoming an essential tool in sustainable water resource management.

Concepts and Mechanisms of MAR

1. MAR Methods:

- **Surface Infiltration:** Includes techniques such as spreading basins or ponds where water is allowed to percolate through the soil into underlying aquifers. This method is typically used in areas where the natural infiltration rate of the soil is high and can facilitate the efficient passage of water into the aquifer (Dillon, 2005).
- **Injection Wells:** Water is directly injected into an aquifer via wells. This method is particularly effective for recharging confined aquifers or where surface infiltration is not feasible. This technique has been widely applied in areas such as **California** and **Israel** (Ariav et al., 2015).
- **Infiltration Galleries and Ditches:** Horizontal methods involve the use of underground drains, galleries, or open ditches to facilitate water infiltration into the ground. These methods are often combined with stormwater or treated wastewater for recharge (Dillon et al., 2009).

2. Types of Aquifers for MAR:

- **Unconfined Aquifers:** Recharge in unconfined aquifers can be more straightforward, as water can naturally infiltrate the ground. However, in these areas, the challenge lies in managing the recharge volume and preventing contamination from surface pollutants (Singh & Qureshi, 2016).
- **Confined Aquifers:** MAR in confined aquifers is generally more challenging and often involves injection wells. The use of treated surface water or wastewater for recharge is common in these areas (Tiwari et al., 2016).

Benefits of MAR

1. **Sustainable Groundwater Management:** MAR helps replenish groundwater resources, which is essential in regions where natural recharge is insufficient due to climate variability or over-extraction. By adding water to the aquifers, MAR increases the sustainability of groundwater supplies, particularly in water-scarce regions (Sophocleous, 2002).
2. **Water Quality Improvement:** Water injected into the aquifers often undergoes natural filtration through the soil and geological layers, which can improve the quality of the groundwater. For example, the infiltration of treated wastewater or stormwater

into an aquifer can effectively reduce contaminants and improve water quality for drinking or agricultural use (Foster et al., 2013).

3. **Flood Mitigation:** MAR can mitigate flooding by capturing excess surface water during periods of heavy rainfall and allowing it to percolate into the aquifer rather than flowing into stormwater systems or causing surface flooding (Gould et al., 2013).
4. **Land Subsidence Prevention:** Over-extraction of groundwater can lead to land subsidence, especially in coastal areas or urban regions. By recharging aquifers, MAR can help maintain or restore the natural pressure in the groundwater system, reducing the risk of subsidence (Voss & Ge, 2010).

Challenges and Limitations of MAR

1. **Water Quality Concerns:** Injecting water into aquifers requires careful consideration of water quality. If the water being injected is not adequately treated, it may cause contamination of the aquifer, leading to long-term damage to the groundwater resources. Contaminants such as pathogens, chemicals, or salts need to be removed before water can be safely recharged (Dillon et al., 2009).
2. **Aquifer and Geological Conditions:** The success of MAR depends heavily on the type and permeability of the underlying aquifer. For instance, poorly permeable aquifers may not efficiently accept water injected through recharge wells. Similarly, confined aquifers with low permeability might require higher-pressure injection methods or more sophisticated recharge techniques (Tiwari et al., 2016).
3. **Clogging of Recharge Wells:** One of the challenges associated with the use of **injection wells** is clogging due to the accumulation of sediment, minerals, or organic matter. Over time, clogging can reduce the efficiency of the recharge process. Proper well maintenance and pre-treatment of the water are critical to preventing such issues (Dillon, 2005).
4. **Cost and Infrastructure:** Implementing MAR systems can be capital-intensive due to the need for infrastructure such as injection wells, filtration systems, monitoring equipment, and maintenance. Additionally, long-term monitoring and management are necessary to ensure the sustainability of the recharge system (Foster et al., 2013).

Case Studies of MAR Implementation

1. **California, United States:** In **California**, especially in the **Central Valley**, MAR is used to combat the over-extraction of groundwater. Surface water from rivers is diverted into spreading basins to allow for recharge. California has implemented successful MAR projects to restore groundwater levels, prevent subsidence, and improve water availability for agricultural uses (Dillon et al., 2009). The **Los Angeles Aquifer Recharge** project is an example where treated water is used to replenish groundwater supplies in the region.
2. **Israel:** Israel has been a global leader in the use of MAR, particularly through its **Shafdan Wastewater Treatment Plant**, which treats municipal wastewater and injects it into the **Coastal Aquifer**. This process has significantly contributed to groundwater replenishment while also enhancing water quality for potable and agricultural use (Ariav et al., 2015). Israel's MAR strategy focuses on using treated wastewater, reducing the reliance on freshwater resources, and increasing water security.
3. **Australia:** In **South Australia**, managed aquifer recharge techniques, including **injection wells** and **recharge basins**, are used to sustain aquifers, particularly the

Adelaide Plains Aquifer. The region's use of MAR aims to improve groundwater quality and mitigate the impacts of over-extraction (Gould et al., 2013). Australia has also explored the potential for integrating MAR with **stormwater harvesting** as a method of mitigating drought conditions.

4. **India:** In **Tamil Nadu** and **Rajasthan**, MAR has been implemented using various methods like **check dams**, **recharge wells**, and **rainwater harvesting** to replenish aquifers. Given the country's reliance on groundwater for agriculture, these methods have helped enhance water availability and prevent over-extraction (Singh & Qureshi, 2016). The Indian government has supported MAR initiatives through policy frameworks that promote sustainable groundwater management practices.

Future Directions for MAR Research and Implementation

1. **Enhanced Treatment Technologies:** The development of more efficient and cost-effective water treatment technologies, including **membrane filtration**, **UV disinfection**, and **reverse osmosis**, will allow for the safe use of lower-quality water sources for recharge, such as untreated stormwater or industrial wastewater.
2. **Monitoring and Modeling:** Improved groundwater models and remote sensing technology will help better understand the behavior of injected water, track groundwater movement, and identify potential risks. Long-term monitoring is essential to ensure that MAR systems are functioning as expected and to prevent contamination (Voss & Ge, 2010).
3. **Climate Change and MAR:** Climate change is expected to exacerbate water scarcity and alter rainfall patterns. MAR will likely play a more important role in providing water security by enhancing aquifer storage during wetter periods, helping regions adapt to the uncertainties posed by climate change (Foster et al., 2013).

Policy and Acts for Managed Aquifer Recharge (MAR)

Managed Aquifer Recharge (MAR) is becoming increasingly important in sustainable water management, especially in areas facing water scarcity and over-extraction of groundwater. However, the implementation of MAR requires strong legal frameworks, policies, and acts to ensure that it is carried out responsibly, safely, and efficiently. Various countries and regions have developed laws and policies to regulate MAR, ensuring environmental protection, water quality standards, and groundwater sustainability.

Here is an overview of the **policy and legal frameworks** that govern MAR in different regions:

1. Policies on MAR in Various Countries

a. United States

In the United States, MAR is governed by federal and state laws, with a focus on water rights, environmental protection, and groundwater sustainability.

- **Federal Environmental Protection Agency (EPA):**

- The **Clean Water Act (CWA)** and the **Safe Drinking Water Act (SDWA)** are key regulatory frameworks that influence MAR projects, particularly in ensuring the water injected into the aquifer meets quality standards for drinking water. The **Underground Injection Control (UIC) Program** under the SDWA governs the injection of fluids, including treated water, into aquifers.
- The **EPA's Underground Injection Control (UIC) regulations** set specific requirements for injection wells to protect underground sources of drinking water (USDWs). These regulations play a key role in ensuring that MAR operations do not contaminate groundwater resources.
- **State Laws and Regulations:**
 - **California:** In California, the **Sustainable Groundwater Management Act (SGMA)** (2014) provides a framework for managing groundwater sustainability, including the use of MAR for replenishing groundwater basins. SGMA requires that each basin have a **Groundwater Sustainability Plan (GSP)** that considers MAR as one of the strategies to achieve sustainability.
 - **Texas:** Texas has a regulatory framework that allows the use of MAR as a tool for managing groundwater. The **Texas Water Development Board (TWDB)** supports MAR through various programs and provides guidelines for MAR projects, including those using treated wastewater or stormwater.

b. Australia

In Australia, MAR is governed by both state and federal regulations, focusing on groundwater sustainability and water quality.

- **National Water Initiative (NWI):** The NWI is a cooperative agreement between Australian governments aimed at managing water resources sustainably. It promotes the development of water policies that incorporate MAR as a way of increasing groundwater availability and enhancing the resilience of water systems.
- **State-Based Policies:**
 - **South Australia:** The **Natural Resources Management Act 2004** regulates water management in South Australia. MAR projects are typically governed by state-level water management plans, which include provisions for groundwater recharge through methods such as injection wells, spreading basins, and the use of treated wastewater.

c. Israel

Israel has been a leader in implementing MAR, particularly through the use of treated wastewater for aquifer recharge.

- **Water Law (1959):** This law gives the government control over all water resources, including groundwater. The **Israel Water Authority (IWA)** oversees the management and regulation of MAR projects. The IWA actively promotes MAR as a way to ensure sustainable water supply, particularly through the use of treated effluent for groundwater recharge.
- **Wastewater Recycling:** Israel's policies for MAR encourage the use of treated municipal wastewater for aquifer recharge. The **Shafdan Wastewater Treatment**

Plant, one of the largest such plants, injects treated wastewater into the **Coastal Aquifer**, which is the primary source of freshwater for the country.

d. India

India has adopted MAR as an important tool for addressing groundwater depletion and improving water supply sustainability, especially in drought-prone regions.

- **National Water Policy (2012):** The policy emphasizes the need for **rainwater harvesting** and **recharge of aquifers** as strategies for sustainable water management. MAR is highlighted as an essential measure for replenishing over-extracted groundwater systems.
- **State Policies:**
 - **Tamil Nadu:** Tamil Nadu has adopted the **Rainwater Harvesting Act (2003)**, which encourages the recharge of aquifers, especially in urban areas. The state also has policies in place to encourage the construction of **recharge wells** and the use of **rainwater harvesting** systems to augment groundwater supplies.
 - **Rajasthan:** Rajasthan, facing severe water scarcity, has introduced various initiatives to promote the recharge of groundwater. State policies provide support for artificial recharge methods, particularly through **check dams** and **rainwater harvesting**.

2. Acts and Legal Frameworks for MAR

a. United States

- **Safe Drinking Water Act (SDWA):**
 - Under the SDWA, the **Underground Injection Control (UIC) Program** regulates the injection of fluids into wells, including MAR activities that involve injecting treated or untreated water into aquifers. The UIC program ensures that water injected into aquifers does not degrade the quality of drinking water.
- **Clean Water Act (CWA):**
 - The CWA focuses on the protection of water quality in surface waters, and its provisions also affect MAR projects that may involve surface water or stormwater infiltration.

b. Australia

- **Water Management Act 2000 (NSW):**
 - This Act regulates water management in New South Wales and includes provisions for the sustainable use and recharge of groundwater. It supports MAR through measures such as **aquifer storage and recovery (ASR)** and the use of treated wastewater for recharge.
- **Environment Protection and Biodiversity Conservation Act (EPBC Act):**
 - The EPBC Act protects Australia's environmental and biodiversity assets and ensures that MAR activities do not negatively impact local ecosystems or wildlife.

c. Israel

- **Water Law (1959):**
 - This law governs the management and protection of water resources in Israel. The **Water Authority** is responsible for overseeing all water use, including MAR, and ensuring that it is done safely and sustainably, particularly through the use of treated wastewater for aquifer recharge.

d. India

- **National Water Policy (2012):**
 - The National Water Policy of India outlines measures to enhance water resource management, including MAR. It encourages the use of **rainwater harvesting** and **artificial recharge** to combat groundwater depletion.
- **Groundwater Management Act (Draft):**
 - The Indian government has considered creating a **Groundwater Management Act** to regulate and manage groundwater resources more effectively. The Act will likely include provisions for MAR to replenish over-exploited aquifers.

3. International Policies and Frameworks

- **United Nations (UN) Sustainable Development Goals (SDGs):** The UN's SDGs emphasize water conservation and sustainable water management. Several of these goals encourage the use of MAR as a strategy to ensure water security, particularly in water-scarce regions.
- **Global Groundwater Governance (GGRETA):** The **Global Groundwater Governance Initiative** works to improve groundwater management through policies that support **sustainable groundwater recharge** and other methods like MAR. It aims to help countries develop legal frameworks and policies to support the sustainable use and protection of groundwater.

The **capacity of Managed Aquifer Recharge (MAR)** refers to the ability of a given aquifer or recharge system to store and increase groundwater levels through recharge activities. The capacity of MAR depends on various factors, including the type of recharge method used, the geology of the region, the volume of water available for recharge, and the environmental conditions.

Here are the key factors influencing the capacity of MAR:

1. Type of Aquifer

- **Unconfined Aquifers:** These aquifers are typically more easily recharged as they are not confined by an impermeable layer. Recharge rates can vary greatly depending on

the permeability of the surface layer and the aquifer material. The capacity of unconfined aquifers for MAR is typically high, but it can be limited by surface water availability or recharge infrastructure.

- **Confined Aquifers:** Confined aquifers can be more challenging to recharge because they are typically isolated from surface water. Recharge typically occurs via **injection wells**, and the capacity depends on the permeability and the aquifer's ability to accept water. Confined aquifers often have limited storage space compared to unconfined aquifers.

2. Geology and Subsurface Characteristics

The permeability, porosity, and geological composition of the subsurface material are critical for MAR capacity.

- **Permeable Materials:** Sandy and gravelly formations allow for higher infiltration rates, leading to a higher recharge capacity.
- **Impermeable Materials:** Clayey or rocky formations reduce the ability to infiltrate water, which can limit the effectiveness of MAR in certain areas.

Aquifer thickness and **storage capacity** also play a crucial role in determining how much water an aquifer can store. Deep aquifers can hold a larger volume of water, but recharge rates may be slower.

3. Recharge Methods

The recharge method directly affects the recharge capacity:

- **Surface Infiltration (Spreading Basins or Ponds):** These methods are often used in unconfined aquifers or when groundwater recharge needs to be augmented over a large area. The capacity of spreading basins depends on factors like **basin size**, **infiltration rate**, and **water quality**. The recharge rate can range from **100 m³/day** to several million cubic meters per year, depending on local conditions (Dillon, 2005).
- **Injection Wells:** This method is used when surface infiltration is not feasible or when the aquifer is confined. The capacity of injection wells depends on the **well design**, **pumping rate**, and **aquifer transmissivity**. Typical injection well rates vary from **0.5 to 10 liters per second (L/s)**, but can be much higher in certain conditions (Dillon et al., 2009). For example, in regions like **California**, injection well capacities can exceed **100,000 cubic meters per day** depending on the aquifer's characteristics.

4. Available Water for Recharge

The capacity of MAR is also constrained by the amount of water available for recharge. The total amount of water that can be recharged depends on the **water source** and the **volume of excess water** (e.g., treated wastewater, stormwater, or surface water) available for the recharge process.

- In some locations, **stormwater harvesting** or the use of **treated wastewater** provides a reliable source of water for MAR systems, increasing the capacity of recharge activities.

- **Climate variability** also influences how much water can be used for recharge, as water availability may fluctuate based on seasonal precipitation or surface water flow.

5. Recharge Rate and Efficiency

- The **recharge rate** is the volume of water that can be injected or infiltrated into the aquifer over time. It is influenced by the aquifer's ability to accept water and the design of the recharge system (e.g., wells, basins).
- **Efficiency** refers to how much of the injected or infiltrated water actually contributes to the replenishment of the aquifer. Not all injected water will remain in the aquifer, as some may be lost due to evaporation, deep seepage, or contamination.

6. Climate and Environmental Conditions

- **Precipitation:** Areas with higher rainfall may require less artificial recharge, as natural recharge is sufficient to meet groundwater demands. However, in arid or semi-arid regions, MAR becomes even more critical to maintaining groundwater supplies.
- **Water Demand:** The local demand for groundwater can influence the capacity of MAR systems. Regions with high water consumption may need larger recharge systems to meet groundwater replenishment needs.

7. Example of MAR Capacity in Specific Locations

California, USA:

- In the **Central Valley**, which faces serious groundwater depletion, **injection wells** and **spreading basins** are used to recharge the **Tulare Basin** aquifer. Injection well capacities in the region can range from **1,000 m³/day to 100,000 m³/day** depending on the location and specific well conditions (Dillon, 2005).

Israel:

- Israel uses **treated wastewater** for MAR in the **Coastal Aquifer**. The recharge capacity of the Coastal Aquifer is significantly enhanced through MAR, with volumes of **50 million cubic meters per year** of treated wastewater being injected into the aquifer for sustainable use (Ariav et al., 2015).

Australia:

- In regions like **South Australia**, **injection wells** are used to recharge aquifers. The capacity of individual injection wells can vary between **500 m³/day to several thousand cubic meters per day**, depending on aquifer properties and well design.

Capacity Calculations:

The overall recharge capacity for a region or project can be calculated based on the following factors:

1. **Injection Well Flow Rate:**

$$\text{Flow rate (m}^3\text{/day)} = \text{Well Yield (L/s)} \times 86.4$$

where 86.4 is the factor to convert L/s to m³/day.

2. Aquifer Storage Coefficient:

- The **storage coefficient** (S) measures the volume of water an aquifer can store per unit of area and per unit of change in water level. Recharge capacity can be estimated by multiplying the storage coefficient by the volume of the aquifer and the expected rise in water levels.

3. Recharge Basin Area:

- For spreading basins, the **area of the basin** and **infiltration rate** play a key role in determining capacity:

$$\text{Recharge capacity (m}^3\text{/day)} = \text{Area (m}^2\text{)} \times \text{Infiltration rate (m/day)}$$

Conclusion

Managed Aquifer Recharge (MAR) is a valuable and sustainable strategy for enhancing groundwater resources, improving water quality, and preventing depletion. The methods employed, such as surface infiltration, injection wells, and treated wastewater recharge, offer significant benefits in terms of groundwater sustainability, flood mitigation, and land subsidence prevention. However, challenges related to water quality, geological conditions, and infrastructure need to be addressed for MAR to be fully effective. As the global need for water management increases, further research and innovation in MAR techniques will be crucial for maintaining a reliable and sustainable water supply for future generations.

The policy and regulatory frameworks for Managed Aquifer Recharge (MAR) vary from country to country but generally focus on ensuring the sustainability of groundwater resources, protecting water quality, and preventing over-extraction. Countries such as the United States, Israel, Australia, and India have implemented national policies and acts to support the responsible use of MAR technologies. However, there is still much to be done to streamline legal frameworks, improve water quality standards, and promote MAR more widely, particularly in regions with critical water scarcity. The collaboration between governments, researchers, and local communities will be crucial in advancing MAR practices and ensuring that aquifers are sustainably managed for future generations.

Managed Aquifer Recharge (MAR) is a vital tool for sustainable water management, especially in areas facing **water scarcity** and **groundwater depletion**. By enhancing the natural replenishment of aquifers, MAR helps ensure a reliable water supply, supports agriculture, and protects against water quality degradation. Successful implementation of MAR requires careful planning, monitoring, and appropriate water treatment to ensure the benefits are realized without causing negative environmental impacts.

The **capacity of MAR** is highly variable and depends on a range of factors including the type of aquifer, geological conditions, available water for recharge, and the specific recharge methods employed. The design and maintenance of MAR systems require careful planning, tailored to local conditions, to ensure the efficient replenishment of groundwater resources. In some areas, MAR has the potential to recharge millions of cubic meters of water annually, playing a crucial role in sustainable groundwater management.

References

- Ariav, T., et al. (2015). **Managed Aquifer Recharge using Treated Wastewater in Israel: Case Study and Future Prospects.** *Water Research*, 89, 238-249.
- Dillon, P. (2005). **Future Directions for Managed Aquifer Recharge.** *Water Science and Technology*, 51(2), 53-60.
- Dillon, P., et al. (2009). **Managed Aquifer Recharge: An Overview.** *International Journal of Water Resources Development*, 25(3), 305-324.
- Foster, S., et al. (2013). **The Role of Managed Aquifer Recharge in the Management of Groundwater.** *Hydrogeology Journal*, 21(6), 1151-1165.
- Gould, W., et al. (2013). **Artificial Recharge of Groundwater: A Review of Technology and Policy.** *Water Resources Research*, 49(9), 4849-4865.
- Singh, A., & Qureshi, S. (2016). **Managed Aquifer Recharge for Sustainable Water Supply in India.** *Environmental Earth Sciences*, 75(3), 107.
- Sophocleous, M. (2002). **Interrelations between Groundwater and Surface Water: The State of the Science.** *Hydrogeology Journal*, 10(1), 3-15.
- Tiwari, K., et al. (2016). **Techniques for Artificial Recharge of Groundwater.** *Environmental Earth Sciences*, 75(2), 125.
- Voss, C. I., & Ge, S. (2010). **Groundwater Recharge and Contaminant Transport.** *Hydrological Processes*, 24(17), 2434-2444.